

2010/9/17 Toyota Matching Data

F:front R:rear F/R:front and rear same AL: aluminium MG: magnesium

Please bear in mind that old cars may have modified parts already fitted that may make this data incorrect. Check the hub size, PCD and thread pitch of your studs before ordering.

Model	Chassis type	Variant	PCD	Normal option	Larger option	Notes
Celica	TA-22 RA-21	.	114.3-4	F: B 14-65 +14.5 B 14-70	R: F/R: F8 15-65 +14.5	.
Celica LB	.	.	114.3-4	F: B 13-65 +14.5 70	R: B 13- 70 F: A 14-65 +9.5 R: A 14-70 +3	.
Celica xx (Mk1 Supra)	MX45/46	.	114.3-4	F/R: B 14-65 +14.5	F: F8 15-65 +14.5 R: F8 15-70 +15	.
	MA55/56	.	114.3-4	F/R: B14-65 +14.5	F: F8 15-65 +14.5 R: F8 15-70 +15	.
	GA61/63	.	114.3-4	F/R: B 14-65 +14.5 F/R: F8 15-65 +14.5	F: F8 15-70 +15 R: F8 15-75 +8.5	Up to 195 tyre
	AA61/63	.	114.3-4	F/R: B 14-65 +14.5 F8 15-65 +14.5	F/R: F: F8 15-70 +15 R: F8 15-75 +8.5	.
Celica FWD/4WD	T160	.	100 -5	F/R: F8F 15-65 +40	R: F8F 15-70 +40	.
	.	.		F/R: F8F 14-60 +40	F/R: F8F 15-65 +40	.
	ST180/183	.		F/R: F8F 15-65 +40	R: F8F 15-70 +36	.
	.	.		F: F8F 16-70 +40 R: F8F 16-70 +35	.	205/55-15
	ST185H	GT-FOUR A		F/R: F8F 16-80 +35	R: F8 16-80 +25	.
	ST202	.4WD		F/R: F8F 15-70 +36	F/R: F8F 16-70 +27	.
	ST205	.		F/R: F8F 16-80 +30	.	.
	ZZT23x	SS-II		F/R: F8F 16-70 +35 F8F 17-70 +35	F/R: F/R: F8 17-80 +35	Not suitable for superstrut model

Starlet	KP61	.	114.3-4	F/R: A 12-55 +12 R: A 12-60 +5.5	F: <a href="#">B 13-55 +16</a> +21 R: B 13-60	B type needs 5mm spacer
		.	114.3-4		F: B 14-55 +15 +20 R: A 14-60	
	EP71 turbo	.	100 -4	F/R: F8F 14-60 +35	F/R: F8F 15-60 +35	175 tyre
	EP71 (NA)	.	100 -4	F/R: CV 13-55 +32	.	175 tyre
	EP82	.	100 -4	<a href="#">F/R: F8F 14-60 +35</a>	F/R: F8F 15-65 +35	185/60-14
	EP92	.	100 -4	F/R: F8F 14-60 +35	.	.
MR2	AW10/11	.	100 -4	F/R: F8F 14-65 +30	<a href="#">F/R: F8F 15-65 +35</a>	.
		Supercharger	100 -4	F/R: F8F 14-65 +30	.	6J needs 5mm spacer
	SW20 (early)	.	114.3-5	F: F8F 15-70 +36 R: F8F 15-75 +42	<a href="#">F: F8 16-70 +30</a> R: <a href="#">F8 16-80 +30</a>	F:255/50 R:255
	SW20 (late)	.	114.3-5	F: F8F 16-70 +35 R: F8F 16-80 +35	.	.
Corolla FX	AE81/82	.	100 -4	F/R: F8F 14-60 +40	.	.
	AE91/92	.	100 -4	F/R: F8F 14-60 +35	.	.
	AE92	.	100 -4	F/R: F8F 14-60 +35	.	.
Soarer	MZ10	.	114.3-4	F/R: F8 15-65 +19.5	F: F8 16-70 +25 R: F8 16-80 +25	205-255
	GZ20	.	114.3-5		F: F8F 16-70 +40 R: F8F 16-75 +40	.
	MZ20/21	.	114.3-5	F/R: F8F 15-70 +35	R: F8F 16-80 (+50)	.
	JZZ30 JZZ32	.	114.3-5	F/R: F8F 16-80 +35	.	.
Supra	GA70 (narrow body)	.	114.3-5	F/R: F8F 15-70 +40 R: F8F15-75 +35	F: F8F 16-70 +40 R: F8F 16-80(+50)	F205/55 R255/50
	MA70/JZA70 (wide body)	.	114.3-5	F: F8 16-80 +30 R: F8 16-90 +30	.	.

Carina ED	ST160	.	100 -5	F/R: F8F 14-60 +35	F/R: F8F 15-65 +40	.	
	ST162	.	100 -5	F/R: F8F 15-65 +40	.	.	
	CT170	.	100 -5	F/R: F8F 14-60 +35	.	.	
Carina FR (Corona)	AA63	.	114.3-4	F/R: B 13-60 +21	F: A 14-60 +20 R: B 14-70 +8	.	
Mark II, Chaser, Cresta	GX70/71	.	114.3-4	F/R: F8 15-65 +14.5	F/R: F8 15-70 +15	205/60-15	
	GX81	.	114.3-5	F/R: F8F 15-65 +40	F: F8F 16-70 +40 R: F8F 16-80(+50)	205.225-16	
	JZX90	.	114.3-5	F/R: F8F 15-65 +40	F: F8F 16-70 +35 R: F8F 16-80 +40	205.225/50	
Camry	VZV30	.	100 -5	F/R: F8F 15-65 +40	.	.	
Carina, Celica, Corona	ST202	.	100 -5	F: F8 16-70 +35	R: F8 16-70 +25	205/50-16	
Levin/Trueno	TE27	.	114.3-4	F: B 14-75 +1.5	R: R 14-80 -6	With flares	
	.	.	114.3-4	F: B 14-65 +14.5 R: B 14-70 +8	.	Without flares	
	TE71	.	114.3-4	F/R: A 14-60 +20	F: A 14-60 +20 R: B 14-65 +14.5	.	
	AE86/85	.	.	114.3-4	F/R: B 13-55 +16 F/R: B 13-60 +21 F/R: B 13-65 +14.5	R: A 13-65 +1.5	.
		.	.		F/R: B 14-65 +14.5 F/R: A 14-60 +16	F/R: F8 15-65 +19.5	.
		.	.		F/R: A 14-65 +9.5	F/R: F8 15-65 +14.5	.
		.	.		R: A 14-70 +3 R: B 14-70 +8	R: A 14-70 +3 R: B 14-70 +8	.
AE92	.	.	100 -4	F/R: F8F 14-60 +35	F/R: F8F 15-60 +35 F/R: F8 16-70 +30	205/50-16	
	.	.	100 -4	F/R: F8F 14-65 +35	F/R: F8F 15-65 +35 R: F8 16-70 +25		
	S/C GT-Z	.	100 -4	F/R: F8F 14-60 +35 F/R: F8F	F/R: F8F 15-65 +35		

				14-65 +30		
	AE101	01/06/91	100 -4	F/R: F8F 15-65 +35	.	195/55-15
	AE111	New Levin	100 -4	F: F8F 15-70 +40 R: F8F 15-70 +36	.	F/R 205/50-15
Paseo	.	.	100 -4	F/R: F8F 14-60 +35	F/R: F8F 15-70 +36	.
Estima, Lucida, Emina, Tarago	TCR21W	.		F/R: F8F 15-65 +40	F/R: F8F 16-70 +40	215/65-15
	TCR10G	2WD	114.3-5	F/R: F8F 16-70 +40	.	205/55-16
	TCR10G	2WD	114.3-5	F/R: F8F 16-70 (+45) F/R: F8F 17-70 (+45)	R: F8 17-80 (+50)	.
Estima 4WD	MCR 40 W	4 WD		F/R: F8F 16-70 (+45) 215/60-16	F/R: F8F 17-70 (+45) 215/50-17	.
Aristo	JZS147	.	114.3-5	F: F8F 16-70 +35 R: F8F 16-80 +35	205/60-16 225/50-16	.
Caldina	ST19#	.	100 -5	F/R: F8F 15-65 +35 195/60-15	F/R: F8F 16-70 +35 F/R: F8F 17-70 +35	F/R: F8F 14-60 +35
Landcruiser 80 series	.	.	139.7-6	F/R: R 16-85(-12)	.	.
Hilux	N130W	.	139.7-6	F/R: R 16-85 -6	.	.
Altezza/IS200	SXE10	.	114.3-5	F: F8F 16-70 +40 R: F8F 16-80 +40	F: F8F 16-70 +35 R: F8F 16-80 +35	+35 needs lowered suspension
	GXE10W	.		.	F: F8F 17-75 +40 R: F8F 17-75 +45	
Vitz/Echo	SCP91	.	100 -4	F/R: F8F 17-70 (+45)	F/R: F8F 17-70 +40	205 / 45R17
	SCP10	.		<u>F/R: F8F 15-65 +35</u>	.	.
bB	NCP31	.	100 -4	F/R: F8 15-65 +19.5	F/R: F8 16-70 +30	Gap at rear
Crown Wagon	130 系	.	114.3-5	F/R: F8 16-75 +25	.	.
MR-2 Spider	ZZW30	.	100-4	F/R: F8F 15-65 +35 R:	F: F8F 17-70 +35 215/40	185/55R-15

				F8F 15-70 +36	R: F8 17-80 (+45) 225/40	modification needed
Celsior/LS400	UCF20-21	2 型	114.3-5	F/R: F8F16-70(+32)	.	Normal tyre size
Alphard	ATH10W	4WD	114.3-5	F/R: F8F 16-70 +35 205/65-16	F/R: F8F 17-70 +35	.

Offsets in brackets need to be ordered as a custom offset.

This matching data applies to non-modified cars. Where hub machining is required add \$40 per wheel.

In some cases the centre cap will not fit without modification.